



Your professional security specialist!

FEATURES:

- Powerful high-speed video protocol processor
- MJPEG video compression
- Support two-way audio function
- High-sensitivity CMOS sensor
- Resolution:640 x 480(VGA), 320 x 240(QVGA)
- Video Frame Rate:30fps(QVGA), 15fps(VGA)
- Minimum Illumination:0.5Lux @ F2.0
- IR night vision(Range:10~15m)
- Remote Pan/Tilt rotate(Horizontal:220°,Vertical:90°)
- Supports control P/T through IP network
- Supporting up to 4 users online simultaneously
- Supporting image snapshot, Supports power up action
- Built-in 10M/100M auto MDI/MDIX Ethernet interface
- Frame ratio or Bandwidth can be adjusted
- Light Frequency:50Hz, 60Hz or Outdoor
- Multi-level users management and passwords definition
- Built-in Web server,supports remotely viewing and/or management the camera form a standare Web browser on any computer,anywhere,and at anytime
- Supporting Dynamic IP (DDNS)and UPnP LAN and Internet(ADSL,Cable Modem)
- Giving alarm in cause of motion detection
- Supporting image snapshot
- Supporting multiple network protocols:HTTP/TCP/IP/UDP/STMP/DDNS/SNTP/DHCP/FTP
- Built-in RTOS,supports software download and configuration online,that is convenient for camera updating and management

SPECIFICATION:

Model	IPW50
Image Sensor	
Sensor	¼" Color CMOS Sensor
Resolution	640 x 480 Pixels
Lens	f: 6mm, F 2.0 (IR Lens)
Viewing Angle	60 Degree
Minimum Illumination	0.5Lux @ F2.0
Video/Image Setting	
Video Compression	MJPEG Video Compression
Video Frame Rate	30fps(QVGA), 15fps(VGA)
Resolution	640 x 480(VGA), 320 x 240(QVGA)
Light Frequency	50Hz, 60Hz or Outdoor
Video Parameters	Brightness, contrast
Audio talk-back	Built-in Mic
Communication	
System Interface	10Base-T/100Base-TX Ethernet Port
Supported Protocol	TCP/IP, DHCP, SMTP, HTTP, DDNS, UPNP, PPPoE,FTP,DNS
Physical / Environment	
Pan/Tilt Angle	Horizontal:220 degree & Vertical: 90 degree
Alarm Input	1 Channel on/off input
Alarm Output	1 Channel relay output
Power Supply	5VDC/1A External Power Adapter
Power Consumption	5W(Max.)
Operate Temperature	(0°C ~ 55°C)
Storage temperature	(-25°C ~ 55°C)
PC System Requirement	
CPU	2.0GHZ or above
Memory Size	256MB or above
Display Card	64M or above memory
Supported OS	Microsoft Windows 98/ME/2000/XP/Vista

PACKING LIST



Adapter



Network cable



IPW50



Bracket



CD-ROM



L210*W190*E130mm